

Regular Wire Wrapping Bits and Sleeves



All Bits & Sleeves are Fully Compatible with any Make or Model Wire Wrapping Tool

AWG (inches)						BIT PART No.	SLEEVE PART No.	METRIC (mm)					
Wire Gauge (AWG)	Max Insulation Diameter	Min/Max Terminal Diagonal	Terminal Hole Depth	Effective Radius	Terminal Hole Diameter			Terminal Hole Diameter	Effective Radius	Terminal Hole Depth	Min/Max Terminal Diagonal	Max Insulation Diameter	Wire Gauge (mm)
18	N/A	.060/.073	1.000	.150	.075	BR18	S194	1.90	3.81	25.40	1.52/1.85	N/A	1.00
19	N/A	.042/.073	1.000	.123	.075	BR19	S171	1.90	3.12	25.40	1.07/1.85	N/A	0.91
19-20	N/A	.091/1.122	1.000	.150	.125	BR1920L	S212	3.17	3.81	25.40	2.31/3.09	N/A	.80-.91
20	N/A	.091/1.122	1.000	.150	.125	BR20L	S212	3.17	3.81	25.40	2.31/3.09	N/A	.80-.91
20-22	N/A	.042/0.73	1.000	.123	.075	BR20	S171	1.90	3.12	25.40	1.07/1.85	N/A	.65-.80
22	N/A	.061/.085	1.000	.125	.086	BR22T	S171	2.18	3.17	25.40	1.54/2.15	N/A	0.65
22	N/A	.054/.073	0.750	.117	.075	BR22	S171	1.90	2.97	19.05	1.37/1.85	N/A	0.65
22-24	N/A	.054/.073	1.000	.111	.075	BR224-1	S171	1.90	2.82	25.40	1.37/1.85	N/A	.50-.65
22-24	N/A	.054/.073	0.807	.111	.075	BR224	S171	1.90	2.82	20.50	1.37/1.85	N/A	.50-.65
24	N/A	.024/.043	1.000	.083	.044	BR2444*	S125LN*	1.11	2.10	25.40	0.60/1.09	N/A	0.50
24	N/A	.055/.074	1.500	.100	.075	BR24D	S159	1.90	2.54	38.10	1.39/1.87	N/A	0.50
24	N/A	.055/.074	0.750	.100	.075	BR24	S159	1.90	2.54	19.05	1.39/1.87	N/A	0.50
24-26	N/A	.058/.073	0.750	.100	.075	BR2426	S159	1.90	2.54	19.05	1.47/1.85	N/A	.40-.50
24-26	N/A	.054/.065	1.000	.098	.066	BR2466	S125LD	1.67	2.48	25.40	1.37/1.65	N/A	.40-.50
26	N/A	.054/.073	1.000	.112	.075	BR16903	S159	1.90	2.84	25.40	1.37/1.85	N/A	0.40
26	N/A	.023/.038	0.750	.068	.040	BR2639*	S93LN*	1.02	1.72	19.05	0.58/0.96	N/A	0.40
26	N/A	.058/.073	1.000	.100	.075	BR26	S159	1.90	2.54	25.40	1.47/1.85	N/A	0.40
30-32	N/A	.034/.038	0.750	.064	.040	BR30*	S93*	1.02	1.62	19.05	0.86/0.96	N/A	.20-.25

Extended (5" Long) Bits and Sleeves Regular and Modified

22	N/A	.054/.073	0.750	.117	.075	BR22-5	S171-5	1.90	2.97	19.05	1.37/1.85	N/A	0.65
22-24	N/A	.054/.073	0.807	.111	.075	BR224-5	S171-5	1.90	2.82	20.50	1.37/1.85	N/A	.50-.65
24	N/A	.055/.073	0.750	.100	.075	BR24-5	S159-5	1.90	2.54	19.05	1.39/1.87	N/A	0.50
26	N/A	.058/.073	1.000	.100	.075	BR26-5	S159-5	1.90	2.54	25.40	1.47/1.85	N/A	0.40
26	.031	.023/.038	0.750	.075	.040	BM2640-5*	S93LN-5*	1.02	1.90	19.05	0.58/0.96	0.79	0.40
30	.027	.031/.035	0.750	.064	.036	BM30-5*	S93-5*	0.91	1.62	19.05	0.79/0.89	0.69	0.25

* These tools are recommended for .025" square terminals on 0.100 centers / 0.63 mm on 2.54 mm centers.

Insulated Sleeves

To order insulated sleeves, please specify insulation color on the end of the standard sleeve part number. (i.e. S171R: R=red, B=blue, Y=yellow, G=green, W=white).



JDV Products, Inc • 22-01 Raphael Street • Fair Lawn, NJ 07410 USA
201-796-1720 • Fax 201-796-9399 • www.jdvproducts.com